

PRODUCT FACT SHEET

ProTac® 1L / ProTac® 2L HIGH PERFORMANCE LITHIUM FLASHLIGHT

MARKET

APPLICATIONS: Law Enforcement, Security, Emergency Medical Services, Sporting Goods, Hardware/Tool, Consumer

DESCRIPTION: Compact & powerful, the ProTac® series flashlights offer three different user selectable programs and the

latest in power LED technology. The combination of small size and output from the C4® LED result in one of the brightest tactical personal carry lights for its' size. Packaged with a removable pocket clip and holster.

(Models also available with AA sized cells.)

CASE MATERIAL: 6000 series machined aircraft aluminum with anodized finish. Available in Black.

DIMENSIONS: ProTac® 1L: ProTac® 2L:

WEIGHT: ProTac® 1L: 2.0 oz (57 grams) with battery* ProTac® 2L: 2.8 oz (79 grams) with batteries*

LENS: Glass lens, o-ring sealed.

LIGHT SOURCE: C4® LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: See charts for specific model. Optimized electronics provides regulated intensity.

ON/OFF: Multi-function, push-button tactical tailswitch. One handed operation of momentary, variable intensity or

strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs:

high/strobe/low (factory default), high only, or low/high.

RUN TIME: See charts for specific model. All claims to 10% of initial lumen output.

BATTERY: ProTac® 1L: One (1) 3 Volt CR123A Lithium battery. ProTac® 2L: Two (2) 3 Volt CR123A Lithium batteries.

CR123A batteries have a shelf life of 10 years.

FEATURES: C4® LED technology for extreme brightness.

LED Solid State Power Regulation provides maximum light output throughout battery life.

IPX7 rated design; waterproof to 1 meter for 30 minutes.

2 meter impact resistance tested.

TEN-TAP® programmable switch allows user to select one of three different programs.

Anti-roll facecap. Removable pocket clip.

Serialized for positive identification.

WARRANTY: Streamlight's Limited Lifetime Warranty.

APPROVALS: Meets applicable European Community directives. **CE**

OPTIONAL

ACCESSORIES: Holster.

	ProTac® 1L			ProTac® 2L		
1	FL1 STANDARD	HIGH	LOW	FL1 STANDARD	HIGH	LOW
OUTPUT	31/5	275 LUMENS	22 LUMENS	314	350 LUMENS	30 LUMENS
RUNTIME	Θ	2h	24h	()	3h15m	35h
DISTANCE		143m	41m		159m	49m
INTENSITY		5,100cd	420cd		6,300cd	600cd

All performance claims tested to ANSI/NEMA FL1-2009 Standard

Issued: 12/23/09

Revised: 10/14/16 **Rev:** 8 Made In China **Document #210**

ProTac 2L High Output 266

ProTac 1L High Output 193

277

288

3 3 33

^{*} Battery(s) included with purchase