

STRION[®] HPL

HIGH LUMEN LONG RANGE RECHARGEABLE FLASHLIGHT

MARKET	Descrives Desfancional Links, Low Enforcement, Industrial, Consulty, Outdoor, Consumers
APPLICATIONS:	Premium Professional Light - Law Enforcement, Industrial, Security, Outdoor, Consumer
DESCRIPTION:	Ultra compact & powerful, the Strion [®] HPL rechargeable flashlight offers 3 microprocessor controlled variable intensity modes, strobe mode and the latest in high power LED technology. The combination of rechargeable batteries and the high power LED results in one of the lowest operating costs of any flashlight made.
CASE MATERIAL:	6000 series machined aircraft aluminum with anodized finish. Available in Black.
DIMENSIONS:	Length: 7.00 in (17.78 cm) Major Diameter: 2.20 in. (5.59 cm) Barrel Diameter: 0.95 in. (2.41 cm)
WEIGHT:	7.1 oz (202 grams) with battery
LENS:	Unbreakable polycarbonate lens with scratch-resistant coating. O-ring sealed.
LIGHT SOURCE:	High power LED, white, impervious to shock with a 50,000 hour lifetime.
	See chart. Optimized electronics provides regulated intensity. Deep-dish parabolic reflector produces a long range beam with optimal peripheral illumination.
ON/OFF:	Multi-function, push-button tactical tailswitch. One handed operation of momentary, variable intensity or strobe mode.
RUN TIME: 🕓	See chart. All claims to 10% of initial lumen output. Strobe: 3 continuous hours.
BATTERY:	Lithium Ion with on-board safety control circuit, 3.63V, 2600mAh, rechargeable up to 1000 times.
CHARGING:	Fits existing Strion® chargers. Clamp style charge holder with digital control circuit that prevents overcharge. Fully recharges battery in 3.5 hours and charges battery in product. Charge base LED indication: LED Steady - Charging; LED Blinking - Charged.
	High power LED for extreme brightness. IPX4 rated design; water resistant operation. 2 meter impact resistance tested. LED Charge-continuity indicator on charger base. Compact, snap-in charger mounts in any position. Serialized for positive identification.
WARRANTY:	Streamlight's Limited Lifetime Warranty.
APPROVALS:	CE Meets applicable European Community directives.
	BC CEC Compliant
OPTIONAL ACCESSORIES:	Safety Wands, Holster, Rail Mount, Piggyback® Charger, 6 Unit Bank Charger.

MEDIUM LOW HIGH 615 320 160 OUTPUT LUMENS LUMENS LUMENS RUNTIME 4h 30 min 1h 15min 2h 30min DISTANCE 400m 200m 283m INTENSITY 40,000cd 20,000cd 10,000cd

