## STREMUIGHT

## PRODUCT FACT SHEET

## ProTac® 1L-1AA HIGH LUMEN TACTICAL LIGHT

**MARKET** 

APPLICATIONS: Law Enforcement, Security, Military, Sporting Goods, Hardware/Tool, Consumer

**DESCRIPTION:** Lightweight, compact, high lumen, CR123 Lithium or AA battery powered Tactical Light featuring

the latest in shock-proof power LED technology and three different user selectable programs. The combination of size, output, and battery versatility, result in one of the brightest and versatile everyday

carry lights. Packaged with a removable pocket clip and holster, CR123 and AA alkaline battery.

CASE MATERIAL: 6000 Series machined aircraft aluminum with black anodized finish.

**DIMENSIONS:** Length: 4.25 in. (10.8 cm) Head diameter: .950 in. (2.41 cm) Barrel diameter: .850 in. (2.16 cm)

**WEIGHT:** 2.5 oz (71 grams) with CR123 battery (included in purchase).

2.8 oz (79 grams) with AA alkaline battery (included in purchase).

2.4 oz (68 grams) with AA Lithium battery.

**LENS:** High temperature, shock mounted, AR coated, impact resistant borofloat glass.

LIGHT SOURCE: C4®LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT SOURCE: C4\*LED technology, impervious to snock with a 50,000 nour tiretime.

**LIGHT OUTPUT:** 

350



**CR123 Battery:** 6,400 candela peak beam intensity, 160m beam distance, 350 lumens measured system output on High. 720 candela peak beam intensity, 53m beam distance, 40 lumens measured system output on Low.

AA Alkaline or AA Lithium Battery: 2,750 candela peak beam intensity, 105m beam distance, 150 lumens measured system output on High. 720 candela peak beam intensity, 53m beam distance, 40 lumens measured system output on Low.

**ON/OFF:** Multi-function, push-button tactical tail switch. One handed operation of momentary, variable

intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three

different programs: high/strobe/low (factory default), high only, or low/high.

**RUN TIME:** 



CR123 - High 1 hour 30 minutes, Low 14 hours, Strobe 3 hours.

AA Alkaline - High 1 hour 20 minutes, Low 7 hours 30 minutes, Strobe 3.5 hours.

AA Lithium - High 4 hours 15 minutes, Low 14 hours, Strobe 8 hours.

Run times are to 10% of initial output. Solid-state current regulation for consistent illumination.

BATTERY: One 3 Volt CR123A lithium battery (with a storage life of 10 years), one AA Alkaline battery, or one

AA Lithium Battery.

FEATURES: C4®LED technology for extreme brightness.

IPX7 rated design; water proof to 1 meter for 30 minutes

2 meter impact resistance tested.

LED Solid State Power Regulation provides maximum light output throughout battery life.

Momentary/steady On-Off switch.

TEN-TAP® programmable switch allows user to select one of three different programs.

Serialized for positive identification.

Removable pocket clip.


Holster

APPROVALS: Meets applicable European Community Directives. (6

**WARRANTY:** Streamlight's Limited Lifetime Warranty.

**OPTIONAL** 

ACCESSORIES: None



Issued: 2/23/2016

Revised: 4/12/2016 Rev: 1 Made in China Document #279