

PRODUCT FACT SHEET

Twin-Task® HEADLAMP AA BATTERY-POWERED HEADLAMP

MARKET

APPLICATIONS: Automotive, Sporting Goods, Consumer, Industrial, Law Enforcement, Security, Emergency

Medical Services, Hardware/Tool

DESCRIPTION: With two light sources to choose from, the Twin-Task® Headlamp is a versatile headlamp for any

task. With its 300 lumen main beam for distance spotting and its 250 lumen COB flood LED it has iust the right mode for your lighting needs. It uses the latest in power LED technology and with

five lighting levels, the light is up to any task. Packaged with an elastic head strap.

CASE MATERIAL: Impact modified Nylon. Available in Black/red combination.

DIMENSIONS: Head dimensions: Height 1.35 in. (3.43 cm) Width: 2.125 in. (5.4 cm) Head bracket Length: 2.67

in. (6.78 cm) Maximum Depth (including headband mounting plate): 1.22 in. (3.1 cm)

Rear battery pack dimensions: Height 2.4 in. (6.1 cm) Width: 1.0 in. (2.54 cm) Length: 3.0 in.

(7.62 cm)

WEIGHT: 7.6 oz (215 grams) with alkaline batteries (included with purchase). 6.9 oz (196 grams) with

Lithium batteries.

LENS: Polycarbonate lens, gasket sealed.

LIGHT SOURCE: C4® LED and COB LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT:

300

Regulated output for consistent lumen performance over the battery life.

ON/OFF: Multi-function, push-button switch.

Spot Modes = Low, Medium, High and Off

Flood Modes = Low, High and Off

To change the light (beam) from Spot to Flood, or Flood to Spot, turn the light on, then press and hold the on/off button for three seconds until the light changes light source. Release the button.

Switching Output Modes: Pushing the button within 1.5 seconds of the last button push will change the light mode. You may sequence through all light levels and then to off.

NOTE: If you wait more than two seconds between button pushes, the next press of the button

will turn the light off.

RUN TIME:

See chart. All claims to 10% of initial lumen output.

Three (3) Alkaline or Lithium batteries. **BATTERY:**

FEATURES:

C4® LED technology for extreme brightness. IPX4 rated for water resistant operation. All openings sealed.

2 meter impact resistance tested.

LED Solid State Power Regulation provides maximum light output throughout battery life.

Streamlight's Limited Lifetime Warranty **WARRANTY:**


APPROVALS: CE Meets applicable European Community directives.

OPTIONAL

ACCESSORIES: None

	SPOT			
I	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT	31/5	300 LUMENS	100 LUMENS	50 LUMENS
RUNTIME	0	4h 15m	20h	38h
DISTANCE	M	108m	63m	45m
INTENSITY		2,900cd	1,000cd	500cd
			,	





All performance claims tested to ANSI/PLATO FL1-2016 Standard

Issued: 01/30/2018

Revised: Rev: 0 Made In China Document #319